



ESSEN TUB CFA

Classification: Special Product

Flux-cored wire developed for a wide range of gouging, bevel cutting, and cutting operations on various types of metals. It stands out for its excellent ignition and re-ignition characteristics, delivering a high-intensity arc and strength capable of withstanding high amperage levels.

It offers superior performance, efficiency, and speed during operations. Its ability to perform processes without leaving residues on the beveled surface is remarkable, effectively removing unwanted material from parts, roots or defective welds, as well as cracks, rivets, and bolt heads.

Essential for efficient and high-quality industrial processes. Improved efficiency is achieved when applied through automated processes.

CHEMICAL COMPOSITION:

Not applicable

MECHANICAL PROPERTIES:

Hardness:	Not applicable
-----------	----------------

WELDING CURRENT:	DC+
SHIELDING GAS:	NOT REQUIRED
STICK-OUT (mm):	20 to 50

PRODUCT FEATURES:

DIAMETER (mm):	CURRENT (A):	VOLTAGE (V):	PACKAGING (kg):
2.40	600 to 800	32 to 35	20.0 kg (spool) 200 kg (drum)

CUSTOMER SERVICE POLICY

The information provided above is for reference purposes only and shall not be considered as a guarantee or certificate. Many variables may influence the results of a welding operation. Uniweld Industria de Eletrodos LTDA assumes no responsibility for any incorrect application of the product. If you have any questions, we recommend contacting our Technical Assistance Department for proper support.